２０２５年１０月（２階フロア）の
コンディションは、４６ｆｅｅｔです。

Brunswick / PBA — Official Lane Maintenance and Capital Equipment Provider
DIRECT+ Conditioning System

X	ENVOY
	AUTHORITY22

Select Machine

Pattern Information

Date	2025 10/1
Pattern Type	Recreational
Pattern Difficulty	Medium
Pattern Designer	Terashima
Pattern Volume (ml)	23.55

Surface Information

Surface Type	Synthetic
Surface Brand	
Age	6

Pattern Parameters

Pattern Number	1
Pattern Name	2025 10 所沢
Mode	Clean & Oil
Forward Speed	Max Clean
Start Cleaner Spray	0
Start Squeegee	0
Start Oiling	6
Split Pattern	No

Supplies Information

Lane Cleaner	Brunswick MAX 10	
Cleaner Mixture Ratio	10 : 1	
Cleaner Transition Distance		Authority22
Cleaner Spray End Distance	45	Envoy
Lane Conditioner	Logic と curve 1:1ブレンド	

Notes 今月のレーンコンディションは 46F です。

Zone	1	2	3	4	5	6	7	8
Zone End Distance	6	14	20	26	31	40	46	
Zone Ratio L	3.1 : 1	3.8 : 1	4.1 : 1	5.4 : 1	9.5 : 1	1.0 : 1	### : 1	### : 1
Zone Ratio R	3.1 : 1	3.8 : 1	4.1 : 1	5.4 : 1	9.5 : 1	1.0 : 1	### : 1	### : 1
Zone Volume (ml)	6.25	7.54	4.64	3.33	1.80	0.00	0.00	0.00

ZONE	7 Pin Side																			Board Number										10 Pin Side									
	L1	L2	L3	L4	L5	L6	L7	L8	L9	L10	L11	L12	L13	L14	L15	L16	L17	L18	L19	C20	R19	R18	R17	R16	R15	R14	R13	R12	R11	R10	R9	R8	R7	R6	R5	R4	R3	R2	R1
1	5	5	16	20	31	36	46	56	66	76	86	94	94	94	94	94	94	94	94	94	94	94	94	94	94	94	94	94	86	76	66	56	46	36	31	20	16	5	5
2	3	3	9	14	24	29	39	49	59	69	79	88	88	88	88	88	88	88	88	88	88	88	88	88	88	88	88	88	79	69	59	49	39	29	24	14	9	3	3
3	2	2	5	10	18	23	33	43	53	58	63	68	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	68	63	58	53	43	33	23	18	10	5	2	2
4	1	1	4	6	9	14	19	24	29	39	44	49	54	57	57	57	57	57	57	57	57	57	57	57	57	57	54	49	44	39	29	24	19	14	9	6	4	1	1
5	1	1	2	2	4	6	9	14	14	19	24	29	34	39	39	44	44	44	44	44	44	44	44	44	39	39	34	29	24	19	14	14	9	6	4	2	2	1	1
6	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
8																																							







3L-7L:18L-18R	Ratio by Total Volume	18L-18R:7R-3R
4.12	1	4.12